



N450 Wireless Access Point TEW-690AP (V1.0R)

TRENDnet's N450 Wireless Access Point, model TEW-690AP, supports Access Point, Wireless Distribution System (WDS), and Repeater mode functionality.

Advanced Multiple Input Multiple Output (MIMO) antenna technology with three spatial streams per antenna, generates a maximum theoretical wireless throughput of 450Mbps and exceptional wireless coverage.

A Gigabit Ethernet port maintains high performance wired connections. Wi-Fi Protected Setup (WPS) integrates other WPS supported devices at the touch of a button. Advanced features include 4 SSIDs per wireless band, different encryption for each SSID, WMM Quality of Service data prioritization, WPA2-RADIUS encryption, and a convenient on/off power switch.

FEATURES

- High performance 450Mbps wireless n access point
- 1 x 10/100/1000Mbps Auto-MDIX Gigabit LAN port
- 1 x WPS button
- 1 x Reset button
- On/off power switch (EU Version)
- Diagnostic LEDs
- Wi-Fi compliant with IEEE 802.11n standard
- Backwards compatible with IEEE 802.11g/b devices
- Features Wireless Distribution System (WDS) and Repeater modes for wireless network expansion
- Supports 64/128-bit WEP, WPA/WPA2-PSK, and WPA/WPA2-RADIUS wireless security
- Mac filter feature for added security
- Wi-Fi Multimedia (WMM) Quality of Service (QoS) data prioritization
- Multiple Input Multiple Output (MIMO) antenna technology
- Define up to 3 additional SSIDs
- One touch wireless connection using the WPS button
- Maximum reliability, throughput, and connectivity with automatic data rate switching
- Easy user setup wizard and intuitive Web browser configuration
- Coverage of up to 100 meters indoor (328ft.) and 300 meters outdoor (948ft.) *
- 3-year limited warranty


*Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.

N450 Wireless Access Point TEW-690AP (V1.0R)

SPECIFICATIONS

Hardware	
Standards	• IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.11b, IEEE 802.11g, and IEEE 802.11n
Interface	• 1 x 10/100/1000Mbps Auto-MDIX Gigabit LAN port
LED Indicator	• Wireless, LAN, WPS, Power
Buttons	• Reset button – restores factory default settings • WPS button- enables WPS function • On/off power (EU version)
Power	• 12 V DC 0.5A power adapter
Power Consumption	• 3.8 watts (max)
Dimensions (LxWxH)	• 120 x 84 x 24 mm (4.7 x 3.3 x 1.0 in.)
Weight	• 160 g (5.6 oz.)
Temperature	• Operating: 0° ~ 40° C (32° ~ 104° F); Storage: -20° ~ 60° C (-4° ~ 140° F)
Humidity	• Max. 90% non-condensing
Certifications	• CE, FCC
Wireless	
Frequency	• 2.412 ~ 2.472 GHz
Antenna	• 2.4GHz: 2dBi (built-in on board) • 5GHz: 1dBi (built-in on board)
Data Rate (auto fallback)	• 802.11b: up to 11Mbps • 802.11g: up to 54Mbps • 802.11n: up to 450Mbps
Output Power	• 802.11b: 18dBm (typical) • 802.11g: 15dBm (typical) • 802.11n: 15dBm (typical)
Receiving Sensitivity	• 802.11b: -84dBm (typical) • 802.11g: -72dBm (typical) • 802.11n: -69dBm (typical)
Encryption	• 64/128-bit WEP, WPA/WPA2-PSK, WPA/WPA2-RADIUS
Channels	• 1~ 11 (FCC), 1~13 (ETSI)

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-690AP
- CD-ROM (Utility and User's Guide)
- Multi-Language Quick Installation Guide
- 1 x Cat. 5 Ethernet cable (0.6 m / 2 ft.)
- Power adapter (12V DC, 0.5A)

RELATED PRODUCTS

TEW-691GR	450Mbps Wireless N Gigabit Router
TEW-640MB	300Mbps Wireless N 4-Port Media Bridge
TEW-624UB	300Mbps Wireless N USB Adapter

ORDERING INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
 Tel: 1-310-961-5500
 Fax: 1-310-961-5511
 Web: www.trendnet.com
 Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

